

MICROCOIL VASO-OCCLUSIVE DEVICE WITH MULTI-AXIS SECONDARY CONFIGURATION

CROSS-REFERENCE TO RELATED APPLICATIONS

This application is a Continuation-in-Part of co-pending Application

Serial No. 09/671,021; filed September 26, 2000 Partent Number 6, 605,101

FEDERALLY-SPONSORED RESEARCH OR DEVELOPMENT

Not Applicable

BACKGROUND OF THE INVENTION

This invention relates generally to the field of vascular occlusion devices and methods. More specifically, it relates to an apparatus and method for occluding a blood vessel by embolizing a targeted site (such as an aneurysm) in the blood vessel.

The embolization of blood vessels is desired in a number of clinical situations. For example, vascular embolization has been used to control vascular bleeding, to occlude the blood supply to tumors, and to occlude vascular aneurysms, particularly intracranial aneurysms. In recent years, vascular embolization for the treatment of aneurysms has received much attention. Several different treatment modalities have been employed in the prior art. U.S. Patent No. 4,819,637 - Dormandy, Jr. et al., for example, describes a vascular embolization system that employs a detachable balloon delivered to the aneurysm site by an intravascular catheter. The balloon is carried into the aneurysm at the tip of the catheter, and it is inflated inside the aneurysm with a solidifying fluid (typically a polymerizable resin or gel) to occlude the aneurysm. The balloon is then detached from the catheter by gentle traction on the catheter. While the balloon-type embolization device